

## INTERNALLY ILLUMINATED FISHING ROD

### FIELD OF THE INVENTION

This invention is related to the field of angling equipment and, more particularly, to a fishing rod having an illumination source to assist in identifying rod location and movement during nighttime fishing.

### BACKGROUND OF THE INVENTION

Although very few young sports fans could blurt out the name of the 2002 World Champion Billfish Angler Garvan McColgan, and although you may never see a Nike commercial featuring Kevin VanDam, America's most revered bass fisherman with nearly \$1.5 million in winnings, three B.A.S.S. Angler of the Year awards, an FLW Tour Angler of the Year Crown and the title of the 2001 BASS Master Classic, fishing has, remains, and will continue to be a great sport and recreational activity.

One typically pictures the fishing scene as boys standing on a bridge or pier, bass boats nestled underneath tree branches in a tributary of a lake, or anglers dressed in rubber boots that come up to their chests as they wade through an icy river, snapping their lines in the air. When you picture these scenes, the one common thread will most likely be that each scene includes the sun shining brightly in a blue sky. However, there is a whole world of fishing

that does not typically make it onto the fishing shows aired by ESPN – this is the world of night fishing.

There are countless of reasons why night fishing is such an increasingly popular sport. A few such reasons include the reduction in boat traffic

5 (especially recreational) during the night, work and family schedules being too hectic to get away during the daylight and the desire to take advantage of the cooler temperatures at night. However, the serious anglers know that during the nighttime hours, the angler can gain certain advantages over his or her prey. For instance, when fishing during the daylight, the angler must adjust

10 his or her fishing to deeper water as hot surface temperatures tend to send the fish to deeper waters where there is food and good dissolved oxygen.

However, with night fishing, the fish tend to come closer to the cooler surface of the water. Another huge advantage in night fishing is that fish are naturally drawn to shiny items and lights. Although banned in some states, usually

15 those that have decreasing fish populations, many nighttime anglers engage in “green light” fishing. This helps to make the fishing experience more exciting and, more importantly, more fruitful.

Along with the joy of fishing at night comes a host of problems that arise primarily due to the well known fact that for us mortal human beings, it is  
20 certainly more difficult to see at night than it is during the daylight. Several developments in angling equipment have been introduced to alleviate this inconvenience. Such developments include lighted tackle boxes, safety equipment to alert others of your position, equipment that glows in the dark, and various illumination devices that attach to, or operate in conjunction with  
25 a fishing rod.

One prevalent problem that will quickly become apparent to anyone on their first nighttime angling excursion is the inability to see the fishing rod

and, more importantly, to see when the fishing rod is moving due to action at the other end of the fishing line. Several techniques have been introduced in an attempt to alleviate this problem; however, none of these techniques fully resolve the problem and, in some instances actually result in creating other  
5 problems. For instance, some of the available illuminating techniques for fishing rods are plagued by pitfalls, such as (a) attracting insects, (b) being bulky and cumbersome to install and/or operate, (c) creating a risk of entanglement of the fishing line, and/or (d) adversely effecting the breakdown and storage of the fishing rod.

10 Thus, there exists a need in the art for a technique to provide illumination to a fishing rod that is immune to these, as well as other problems. The present invention provides such a solution and, the manner by which this invention exhibits these advantages will become more apparent in the description which follows, particularly when considered in conjunction with  
15 the accompanying drawings.

#### SUMMARY OF THE INVENTION

The present invention provides a solution to the afore-mentioned problems with relationship to the illumination of a fishing rod. The present invention can be included in various embodiments but in general, operates to  
20 provide illumination across the entire length of the rod, or portions of the rod across the length of the rod, and exists completely internal to the rod.

In one embodiment of the present invention, all or portions of the rod material is manufactured with transparent or translucent material. As an example, the rod can be constructed from a clear epoxy resin to provide the  
25 translucent characteristic for light transmission throughout its entire length. The typical fishing rod includes a hollow core that is tapered from the base end to the tip. The hollow core of such a fishing rod is also tapered resulting in the

core at the base having a larger diameter than the core at the tip. In this embodiment of the invention, a light source is placed at the interior base of the rod and the light is directed up the hollow core towards the tip. The tapered core results in refracting the light waves in a manner that light waves exit  
5 through the transparent or translucent material and thus, illuminates the rod. This embodiment of the invention is particular advantageous in that when the rod is moved, as is typical when a fish is attacking the bait on the end of the fishing line, the refraction of the light waves will be altered and thereby providing a visible indication of the activity.

10 This embodiment of the invention is directed to a fully lighted fishing rod that is capable of producing a unique light reflecting and refracting pattern throughout the length of the tapered hollow rod or shaft and advantageously alleviates the afore-mentioned problems pertaining to nighttime fishing.

In another embodiment of the invention, all or portions of the rod  
15 material is manufactured with transparent or translucent material. A light source is placed at the interior base or tip of the rod and the light is directed respectively up the hollow core towards the tip or down the hollow core towards the base. Internal to the rod, light wave obstructions or refractors are placed in a manner to alter light waves by refracting them external to the rod  
20 and thereby providing illumination to portions of the rod.

In another embodiment of the invention, a tube or light conductor is placed internal to the rod and serves as a conduit for the light source. The tube can have the taper characteristic similar to the core and rod or may employ the use of light obstructions or refractors.

25 In another embodiment, a series of mini light sources are mounted internal to the rod at various locations.

Accordingly, embodiments of the present invention operate to provide a fully or partially illuminated fishing rod, and thereby alleviate or eliminate the problems in the prior art techniques by enabling a fisherman to see the fishing rod while fishing at nighttime.

5        These and other features of the invention will become more apparent from the following specification, particularly when read in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a side view of a typical fishing rod suitable for incorporating  
10    the unique features of the various embodiments of the present invention.

Fig. 2a illustrates an alternative embodiment of the present invention that utilizes angled light refractors within the hollow core of the rod.

Fig. 2b illustrates an alternative embodiment of the present invention that utilizes upright light refractors within the hollow core of the rod.

15        Fig. 3 is a diagram illustrating the provision of a light source in an embodiment in which the light source is located in the base end of the rod and directed towards the tip end of the rod.

#### DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

The various embodiments of the present invention provide a solution to  
20    the afore-mentioned problems with relationship to the illumination of a fishing rod by operating to provide internal illumination to the fishing rod. The present invention can be included in various embodiments but in general, operates to provide illumination across the entire length of the rod, or portions of the rod across the length of the rod, and is completely internal to the rod.

25        Turning now to the figures in which like references represent like elements throughout the several views, the various embodiments of the invention will now be described.

Fig. 1 is a side view of a typical fishing rod suitable for incorporating the unique features of the various embodiments of the present invention. The illustrated fishing rod **10** includes a base end **12** and a tip end **16**. The rod **10** includes an internal hollow core **29** extending from the base end **12** to the tip end **16**. In some embodiments of the invention, the hollow core **29** is tapered in a manner that the diameter of the hollow core **29** at the base end **12** is larger than the diameter at the tip end **16**.

A key aspect of the present invention is the illumination of the rod **10**, or portions of the rod **10** extending between the base end **12** and the tip end **16**. This aspect of the invention can be provided using several techniques; however, the common feature among the various embodiments of the invention is that a light source is internal to the rod **10** and the rod **10** is illuminated by refracting and reflecting the light waves provided from the light source in such a manner as to illuminate all or portions of the rod **10**.

The rod **10** is preferably composed of a light transmitting, translucent, fiber glass, epoxy resin material that is flexible, or alternatively, a composite of fiberglass/graphite. For illustrative purposes only, an exemplary rod **10** can be constructed to have hollow core **29** with a diameter of about 1/2" at the base end **12**, tapering down to a diameter of about 1/16" at the tip end **16**, and a generally uniform wall thickness of from about 1/64" to 1/16".

The overall length may be between about 7 to 7 1/2 feet. The rod **10** can be constructed or fabricated around a mandrel, then withdrawn to reveal a hollow core **29** throughout its length; however, those skilled in the art will appreciate that other techniques can be used to fabricate a rod **10** suitable for the various embodiments of the present invention.

In one embodiment of the present invention, a light source is placed at the base end **12** of the rod **10** and the light waves are directed through the

hollow core **29** towards the tip end **16**. Snell's law is well known in the art and basically states that as light waves pass from a first medium into a second medium, the light waves will be refracted. The amount of refraction will depend on the light conducting characteristics of the two mediums. In the present embodiment of the invention, the air within the hollow core operates as a first medium and the rod **10** operates as the second medium. The tapering shape of the rod's internal core **29** operates to continuously change the incident angle at which light rays strike the internal surface. Rather than freely traveling down the rod, the light rays are refracted outward, producing a glowing appearance distributed down the length of the rod **10**.

Advantageously, this embodiment of the present invention allows an observer to determine when activity is occurring on the fishing line. For instance, when the rod tip end **16** is deflected even slightly, such as from fish bites and nibbles, the refraction of the light waves within the hollow core **29** will be altered. As a result, the light will appear to flicker on and off due to the changing internal incident light ray angles. Thus, the flickering rod serves as an alert device signaling line/pole activity.

Although the natural refraction characteristics of a tapered hollow core **29** provide a preferred embodiment for the present invention, the present invention is not limited to such a configuration. In fact, the present invention anticipates other embodiments that can also provide refractive characteristics to the light waves traveling through the hollow core **29** of the rod **10**. Fig. 2a illustrates an alternative embodiment of the present invention that utilizes angled light refractors within the hollow core of the rod. In this embodiment of the invention, transparent light refractors **50** and **51** are placed within the hollow core **29** of the rod **10** at an angle position. Although for illustrative purposes, only two such light refractors are shown, any number of such

refractors could be included internal to the rod **10**. In operation, as the light waves travel through the hollow core **29** of the rod **10**, they strike the light refractors **50** and **51**. A portion of the light waves travel through the light refractors **50** and **51**, and a portion of the light waves are refracted towards the wall of the hollow core **29** and thus, exit the rod **10** to provide illumination.

Fig. 2b illustrates an alternative embodiment of the present invention that utilizes upright light refractors within the hollow core of the rod. In this embodiment of the invention, transparent light refractors **52** and **53** are placed within the hollow core **29** of the rod **10** at an upright position, or substantially perpendicular to the walls of the hollow core **29**. Although for illustrative purposes, only two such light refractors are shown, any number of such refractors could be included internal to the rod **10**. In operation, as the light waves travel through the hollow core **29** of the rod **10**, they strike the light refractors **52** and **53**. A portion of the light waves travel through the light refractors **52** and **53**, and a portion of the light waves are captured within the light refractor and directed towards the edges of the light refractor. As a result, a glowing ring of light appears at the location of the light refractors **52** and **53**.

Advantageously, the embodiments of the invention illustrated in Figs. 2a and 2b do not depend on the tapered characteristic of the rod **10** to provide the refraction of the light waves. Thus, in these embodiments of the present invention the light source can be present at various locations within the hollow core **29** of the rod. For instance, a single light source can be included in the tip end **16** of the rod **10** and the light waves directed towards the based end **12**. In addition, one or more light sources can be included at various locations within the hollow core **29**, directed with towards the tip end **16** or the base end **12**.



Various other modifications or embodiments of the rod can also be employed. For instance, the entire rod **10** does not have to be translucent or transparent. Instead, portions of the rod **10** can be transparent or translucent and still achieve favorable results. For example, because the intensity of the light waves tends to be a little stronger closer to the light source, the intensity of the illumination effect may not be uniform over the length of the rod **10**.

This condition can be altered to change the light intensity pattern by the application of a coating or gradient pattern, such as by the application of a paint, to selected areas of the rod surface in proximity of the light source.

Thus, the intensity of the illumination can be altered in a manner to provide a more uniform distribution. Furthermore, in some embodiments, it may not be desirable to have a uniform distribution of the illumination. For instance, it may be desirable to only illuminate the tip end **16** of the rod **10**. The various embodiments of the present invention can also be utilized to satisfy this requirement. One such solution is to alter the translucent characteristics of the rod **10** so that the light waves only escape at the tip end **16** of the rod.

Alternatively, this requirement can be satisfied by placing the light source at the tip end **16** of the rod **10** and only utilizing a single light refractor at or near the tip end **16**.

It should also be appreciated that rather than relying on the refractive characteristics of the tapered hollow core **29** or the use of various refractors, a light wave conducting medium, such as a fiber optic cable can be placed internal to the rod **10**. In this embodiment of the invention, the light wave conducting medium operates to carry the light waves throughout the length of the rod **10**. The light wave conducting medium can be structured in a manner to provide similar refractive characteristics for the light waves as described in the other embodiments (i.e., tapered or including light refractors) although

those skilled in the art will appreciate that other mechanisms could also be employed to provide refraction of the light waves.

Refractive characteristics can also be added or enhanced using other techniques, such as applying a phosphor coating to the surface of the hollow core 29, placing ridges or obstructions at various locations on the surface of the hollow core 29, and/or constructing the surface of the hollow core 29 to be rough, irregular or in other manners that will result in providing some refractive characteristics to light waves.

In yet another embodiment, the rod 10 can be fabricated as a solid rod of translucent material. In this embodiment, light waves can be directed through the solid rod from a light source. The light waves will be refracted as they exit the first medium, the rod 10, and enter the second medium, the air surrounding the rod 10. Alternatively, the rod 10 can be fabricated with multiple materials, with each material having a different angle of incidence. For instance, the hollow core 29 could be replaced by a solid core of material having a different angle of incidence than the rod 10. In yet another embodiment, the rod 10 can be manufactured using two or more layers of material having differing angles of incidence.

It should be appreciated that similar performance can be obtained by placing multiple light sources through out the hollow core 29 of the rod 10. For instance, a string of mini light emitting diodes can be placed along the hollow core 29 of the rod. It should also be appreciated that any combination of the above-described techniques could be included in an embodiment of the invention. In addition, the various features or combination of features of the invention can be embodied in a single piece rod or a multi-piece rod.

In the various embodiments described herein, a light source is employed to provide illumination of the rod. As previously described, the light source

can be located at various locations within the rod **10**. In addition, it should be appreciated that the light source can be external to the rod **10** and then directed internal to the rod **10** to create a similar effect. The light source can be provided by various technologies but, the preferred embodiment of the present invention utilizes light emitting diodes (LEDs) or high-intensity LEDs. However, it will be appreciated by those skilled in the art that other technologies could also be employed including, but not limited to, laser technology, florescent technology, halogen technology and incandescent technology.

Fig. 3 is a diagram illustrating the provision of a light source in an embodiment in which the light source is located in the base end of the rod and directed towards the tip end of the rod. In this embodiment, a handle **14** is attached to the base end **12** of the rod **10**. Portions of the interior of the handle **14** are hollow to accommodate the light source, as well as a power source in some embodiments. Thus, in one embodiment, the handle may be a tubular housing **22**. In another embodiment, the handle may simply be a covering of the base end **12** of the rod and the light source is mounted within the base end **12**. In either case, in the preferred embodiment the light source **24** is substantially centrally fixed within the handle. To provide directional control for the light waves, the light source can be mounted within a concave member **26**, where the inner surface **28** is light reflective, such as electroplated nickel. Illumination from the light source, such as a high intensity LED, may be directed by the concave member down the hollow rod towards the rod's tip end **16**.

The light source may be controlled by optics, circuitry, switches and a power source that are either co-located within the handle or that exist external

to the rod **10**. In the preferred embodiment illustrated in Fig. 3, the controlling elements are included within the handle.

To operate the light source **24**, a source of power must be provided. In the various embodiments of the invention, the power source can be located internal to the rod or the handle, or exist externally. In the preferred  
5 embodiment illustrated in Fig. 3, an embedded power source is employed. The end of the tubular housing **22** opposite from the light source **24** is provided with a recessed lighting control mechanism **30**. The recessed lighting control mechanism **30** includes a potentiometer **32** to control the current that is  
10 provided to the light source by the power source **31**. Thus, the intensity of the illumination provided by the light source **24** can be controlled. Control of the potentiometer **32** is by means of a recessed rotary knob **34**, within the recess **36**, that further operates to control the potentiometer between an on and off position. The rotary knob **34** can be fixedly attached or removable.  
15 Specifically, by having the knob recessed, accidental activation of the knob is avoided in the event of one dropping or bumping the fishing rod.

The power source in the illustrated embodiment is provided by one or more dry cell batteries **31**, such as conventional AA batteries, aligned in end-to-end relationship within the tubular housing **22**. The batteries are preferably  
20 biased by spring members **38**, **40**. Those skilled in the art will appreciate that some circuitry may be necessary to properly power the light source from the power source, such circuitry may include various voltage dividers, driver circuitry, biasing circuitry and other circuitry or controls. Such circuitry is well known to those skilled in the art and the present invention is not limited  
25 to any particular circuitry used to provide the power source to the light source.

To complete the electrical circuit for operating the lighting control mechanism **30**, a metal strip **42** lying adjacent the tubular housing wall **44**, and

metal ring **46** about and in communication with the potentiometer **32** is provided. The power is applied to the light source through leads **54** and **55**.

In other embodiments wherein the light source is not located in the base end **12** of the rod **10**, the power must still be provided to the light source **24**.

5 This can be accomplished in several manners, and for illustrative purposes only, examples are being provided. In one embodiment, wires, strips or other conductors can be installed in the hollow core **29** to carry the power supply to the light source **24**. One disadvantage of this technique is realized in fishing rods that consist of two or more shafts that are interconnected. Such a  
10 configuration can result in damaging the wires when the rod is broken down for storage or preventing the breakdown of the rod altogether. This disadvantage can be overcome in another embodiment which utilizes traces, mounted on the internal surface of the hollow core **29** similar to the traces found on a circuit board. For multi-piece rods, the connection between the  
15 rods can be structured in such a manner to connect the traces from one rod section to the next without the risk of shorting the traces or leaving the connections open. It should also be appreciated that the present invention can be embodied in a single shaft rod as well as rods constructed of two or more interconnected shafts.

20 Various embodiments of the present invention have been described. Examples have been provided for descriptive purposes and the described examples should not be used to limit the scope of the present invention. It is recognized that changes, variations and modifications may be made to the various embodiments of the present invention without departing from the spirit  
25 and scope thereof.